



# Trajectory prediction to assess ATM performance: Challenges and limitations identified in SESAR ER project APACHE

Xavier Prats (UPC)  
xavier.prats@upc.edu

Presentation to ENGAGE-KTN:  
Thematic Challenge 2: Data-driven trajectory prediction  
*Castelldefels, Barcelona. Nov 6<sup>th</sup> 2018*  
*APACHE Doc: DIS\_WP6-16*



Founding Members



# Introduction



## The **APACHE** Project

**A**ssessment of **P**erformance in current **A**TM operations and of new **C**oncepts of operations for its **H**olistic **E**nhancement

- SESAR Exploratory Research (ER) Project
- Topic ER-11-2015 (ATM performance)
- Grant Agreement: 699338
- 9<sup>th</sup> May 2016 – 8<sup>th</sup> May 2018



<http://apache-sesar.barcelonatech-upc.eu/>



@Apache\_SESAR

# Objectives of the APACHE project




- Propose a new framework to assess European ATM performance based on **simulation** and **optimisation** tools.
- **Fill some gaps in state-of-the-art** methodologies for ATM performance assessment aiming to better capture and understand:
  - the impact of ATM operations :
    - considering a **wide range of KPAs\***
    - proposing a set of **new** or **enhanced PIs**
    - focusing in current AND future SESAR 2020 **ConOps** (SESAR solutions)
  - the **interdependencies** and **trade-offs** among different KPAs
  - the theoretical **limits** for certain KPAs.

(\*) Equity, Capacity, AU Cost-efficiency, ANSP Cost-efficiency, Environment, Flexibility and Safety.




ATM: Air traffic management – KPA: Key performance area – PI: Performance indicator –  
ATS: Air traffic services – AU: Airspace User – ANSP: Air navigation service provider

# APACHE Framework (Post-ops)



APACHE Framework (Post-ops assessments)

# Trajectory Prediction in APACHE




**Historical (4D) Trajectory**

TP to reconstruct the trajectory  
and estimate trip **fuel** and **cost**

TP/optimisator to generate the  
optimal trajectory baseline

TP: Trajectory Predictor  
PIs: Performance Indicators  
ENV: Environmental Impact  
AU-CE: Airspace User Cost-Efficiency




# Main findings and results


## Environment KPA

**Main Contribution of APACHE: Optimal<sup>1</sup> trajectory** as baseline reference to compute performance indicators (PIs)

**Example: Actual and regulated trajectories crossing FABEC (Jul 28<sup>th</sup> 2016 post-ops)**



**Actual/Planned** trajectory *estimated fuel*  
*minus*  
weather **optimal<sup>1</sup>** trajectory **fuel**



**Actual/Planned** route **distance**  
*minus*  
weather **optimal<sup>1</sup>** route **distance**

<sup>1</sup> Optimal baseline trajectories computed in full free-route airspace, flat-route charges scheme and maximum range operations (i.e. Cost Index = 0)




# Main findings and results

## Environment KPA


**Main Contribution of APACHE: Optimal<sup>1</sup> trajectory** as baseline reference to compute performance indicators (PIs)

**Example: Actual and regulated trajectories crossing FABEC (Jul 28<sup>th</sup> 2016 post-ops)**



**Actual** trajectory estimated fuel minus weather **optimal<sup>1</sup>** trajectory fuel

- <sup>1</sup> But... what is the “best” trajectory?
- And what about environmental inefficiencies **due** to the Airspace User (AU)?



<sup>1</sup> Different optimal baseline trajectories computed in the following conditions:

- **FR CI=0**: Full free route airspace and maximum range operations (Cost Index =0)
- **SR CI=0**: Current structured route airspace and maximum range operations
- **FR CCC CI=0**: Full free route airspace, continuous cruise climbs and maximum range operations
- **SR CI-AU**: Current structured route airspace and Cost Index chosen by the Airspace User
- **FR CI-AU**: Full free route airspace and Cost Index chosen by the Airspace User



# Main findings and results

## Environment KPA

**Main Contribution of APACHE:** Optimal trajectory as baseline reference to compute performance indicators (PIs)

- **Distance-based** performance indicators:
  - ✓ Easier to compute
  - X Cannot capture the inefficiencies in the vertical domain
  - X The same ground distance inefficiency could represent different air distance inefficiency and, therefore, different fuel (and CO<sub>2</sub>) inefficiency.
- **Fuel-based** performance indicators:
  - X More difficult to compute →
    - require fuel estimation from surveillance data
    - require cost index estimation from surveillance data
  - ✓ Directly capture inefficiencies in fuel consumption and therefore CO<sub>2</sub>.
  - ✓ Possibility to de-couple vertical and horizontal trajectory inefficiencies.

Trajectory Prediction Challenge






# Main findings and results


## AU cost-efficiency focus area

**Main Contribution of APACHE:** Optimal trajectory as baseline reference to compute performance indicators (PIs)

**Example:** Actual and regulated trajectories crossing FABEC (Jul 28<sup>th</sup> 2016 post-ops)



**Actual** trajectory *estimated cost*  
 minus  
**SBT** *estimated cost* (\*)



**Actual** trajectory *estimated cost*  
 minus  
 Estimated **cost** of **full free route** with estimated Cost Index (\*)

(\*) Assumptions:

- Cost of fuel: fixed fuel price for all AUs
- Tactical cost of trip time given by the Cost Index
- Cost of delay: model proposed by (Eurocontrol, 2017)

➤ *But... what is the "best" trajectory from the Airspace User (AU) point of view?*




Eurocontrol, 2015 (nov). **Standard Inputs for EUROCONTROL Cost-Benefit Analyses**. Technical Report Ed. 7.0.

# Main findings and results

## AU cost-efficiency focus area


Main Contribution of APACHE: Optimal trajectory as baseline reference to compute performance indicators (PIs)

Example: Actual and regulated trajectories crossing FABEC (Jul 28<sup>th</sup> 2016 post-ops)



Actual trajectory time  
minus

Full free route trajectory time with estimated CI



Actual trajectory estimated cost  
minus

Estimated cost of full free route with estimated Cost Index

CI: Cost Index



# Main findings and results

## AU cost-efficiency focus area

**Main Contribution of APACHE:** Optimal trajectory as baseline reference to compute performance indicators (PIs)

- **Cost-based** performance indicators:
  - X **Difficult** to compute →
    - require **fuel estimation** from surveillance data
    - AU's **cost/business model(s)**: cost of time, delay, fuel, etc.
  - ✓ Possibility to **de-couple** vertical and horizontal **trajectory** inefficiencies
- **Time-based** performance indicators:
  - ✓ **Easier** to compute although **estimation of AU's CI is still needed.**
  - ✓ In line with “Operational Efficiency SESAR ambition target” defined in the **ATM master plan** (flight time reduction)
  - X Not representative of the overall cost for the AU

Trajectory Prediction Challenges

CI: Cost Index



# TP challenges

- Fuel estimation from **surveillance** data
- Cost Index (CI) estimation from **surveillance** data
  - Take-off (or landing) **mass** estimation from **surveillance** data
  - **Thrust** estimation from **surveillance** data
    - ❑ High sensitivity to noise in surveillance data (+ gaps in data)
    - ❑ A pure model-based approach is very sensitive to:
      - ❑ Accuracy/representativeness of aircraft performance model
      - ❑ Accuracy/representativeness of the weather input data
    - Could the estimation be enhanced with data-driven and/or signal processing approaches (e.g. estimating flight intents)?
- **Fuel + CI + (mass + thrust) estimation of planned trajectories**
  - ❑ FPL: very coarse description of the trajectory (difficulty to estimate CLB/DES)
  - ❑ SBT: 4D description, but still need to estimate hidden data (mass, CI,...)
  - Could the estimation be enhanced with data-driven and/or signal processing approaches?

SBT: Shared Business Trajectory – FPL: Flight Plan – CLB/DES: Climb/Descent

- Estimation of AU's **costs** (tactical cost of time, cost of fuel, cost of delay, ...)
- Better capture AUs **preferences** (CI, route choice, etc.)
- Better isolate the **contribution of ANS** to flight inefficiencies
  - ☐ Is the initial SBT (or FPL) really what the AU would like to fly?
  - ☐ Is the AU always planning the “best trajectory”?
  - ☐ Could we identify AUs reactive/preventive behaviours?
  - Difficult to model, could be inferred with data-driven approaches?

# Further reading



**Project Deliverable D1.2: Final project results report**



**Project Deliverable D3.1: Review of current KPIs and proposal for new ones**



**Project Deliverable D3.2: Functional requirements and specifications for the ATM performance assessment framework**



**Project Deliverable D4.1: Report on the availability of the APACHE framework**



**Project Deliverable D5.1: Results from simulation and analysis of results**



X. Prats, C. Barrado, A. Vidosavljevic, D. Delahaye, F. Netjasov and D. Crnogorac. 2017 (Nov). **Assessing ATM Performance with Simulation and Optimisation Tools: The APACHE Project**. In *proceedings of the 7th SESAR Innovation Days*. SESAR JU. Belgrade (Serbia).



F. Netjasov and D. Crnogorac. 2017 (Sep). **Assessment of safety performance indicators of future air traffic management system**. In *proceedings of the XLIV Symposium on operational research*. Zlatibor (Serbia).



Dalmau, R., Melgosa, M., Vilardaga, S. and Prats, X. 2018 (Jun). **A Fast and Flexible Aircraft Trajectory Predictor and Optimiser for ATM Research Applications**. Proceedings of the 8th International Conference on Research on Air Transportation (ICRAT). Castelldefels, Catalonia



Xu, Y., Dalmau, R., Melgosa, M., de Montlaur, A. and Prats, X. 2018 (Jun). **Alternative Trajectory Options for Delay Reduction in Demand and Capacity Balancing**. Proceedings of the 8th International Conference on Research on Air Transportation (ICRAT). Castelldefels, Catalonia.



Netjasov, F. and Crnogorac, D. 2018 (Jun). **Potential Safety Occurrences as Indicators of Air Traffic Management Safety Performances: A network based simulation model**. Proceedings of the 8th International Conference on Research on Air Transportation (ICRAT). Castelldefels, Catalonia



<http://apache-sesar.barcelonatech-upc.eu/>



@Apache\_SESAR



## Trajectory prediction to assess ATM performance: Challenges and limitations identified in SESAR ER project APACHE

---

# Thank you very much for your attention!



This project has received funding from the SESAR Joint Undertaking under the European Union's Horizon 2020 research and innovation programme under grant agreement No [number]



© 2018 APACHE consortium. All rights reserved. Licensed to the SESAR Joint Undertaking under conditions

Founding Members



The opinions expressed herein reflect the author's view only.

Under no circumstances shall the SESAR Joint Undertaking be responsible for any use that may be made of the information contained herein.